

Leica Jogger 20/24 Automatic Levels – Fit for Work



SITE PROOF
by Leica Geosystems

- when it has to be **right**

Leica
Geosystems

Leica Jogger 20/24

Automatic Levels – Fit for Work



**Building and
Civil Engineering**



Profiling



Landscaping



Area Leveling

Leica Jogger 20/24 are the ideal partners for all your daily leveling tasks.

Fit for Work – Great features and great performance

- Choice of magnification: 20x or 24x
- Automatic, air-damped compensator
- Smooth, double-sided endless fine drive for easy and precise targeting
- Horizontal circle with 360° division



Fit for Work – Quality and Endurance

- Water resistant (IP54) for instrument use under harsh environmental conditions
- 1 year warranty and access to the worldwide Leica Geosystems network of service and support centers

Fit for Work – Great Jogger package

Tripod and staff are important parts of any leveling equipment. Get better results with approved original Leica Geosystems tripods and staffs. Ask for the original Leica Jogger package.



	Leica Jogger 20	Leica Jogger 24
Standard deviation per 1 km double-run leveling	2.5 mm	2.0 mm
Telescope		
Telescope image	upright	upright
Magnification	20x	24x
Clear objective lens	36 mm	36 mm
Shortest focusing distance	< 1.0 m	< 1.0 m
Field of view at 100 m	< 2.1 m	< 2.1 m
Multiplication constant	100	100
Additive constant	0	0
Compensator		
Working range	± 15'	± 15'
Setting accuracy (standard deviation)	< 0.5"	< 0.5"
Circular bubble	8'/2 mm	8'/2 mm
Horizontal circle		
Graduation	360°	360°
Interval	1°	1°
Weight (net)	1.5 kg	1.5 kg
Operating temperature range	-20°C to +40°C	-20°C to +40°C

Illustrations, descriptions and technical data are not binding. All rights reserved. Printed in Switzerland – Copyright Leica Geosystems AG, Heerbrugg, Switzerland, 2007. 762679enUS – IX.07 – RDV